

CLAIMS

1 A method of communication between a transmitting node and a receiving node, characterized in that:

5 the transmitting node provides a first group flow having one flow or more based upon a first criterion relating to a sequencing and a second group flow having one flow or more based upon a second criterion relating to a retransmitting control, assigns a first identifier to
10 each flow belonging to said first group flow, said first identifier being unique, and assigns a second identifier to each flow belonging to said second group flow, said second identifier being unique; and

the transmitting node classifies the packets, which
15 were input, into one flow or more belonging to said first group flow, based upon said first criterion, yet classifies them into one flow or more belonging to said second group flow, based upon said second criterion, affixes to said packets said first identifier, a first
20 sequential number, said first sequential number being unique within flows specified by said first identifier, said second identifier, a second sequential number, said second sequential number being unique within flows specified by said second identifier, and transmit them;

25 the receiving node classifies all received packets

based upon the second identifier, and checks the packets having the second sequential number, which were not received, with each second group flow, and requests the transmitting node of retransmission thereof;

5 the transmitting node retransmits the packets of the second group flow having the second sequential number requested by the receiving node; and

 the receiving node classifies all received packets based upon the first identifier, sequences the packets
10 within each first group flow based upon the first sequential number, and performs a receiving process of the sequenced packets in the sequenced order.

2 The communication method according to claim 1,
15 characterized in that the transmitting node and the receiving node are connected via one communicating path, the second group flow of the transmitting node is comprised of a single flow, and the packets are transmitted by utilizing a single communicating path.

20

3 The communication method according to claim 1,
characterized in that in a case where a plurality of communicating paths for transmitting the packet exist, the transmitting node selects the communicating path for
25 transmitting the packet, based upon a third criterion

relating to a schedule of the packet transmission.

4 The communication method according to claim 3,
characterized in that the transmitting node and the
5 receiving node are connected via a plurality of
communicating paths, and the transmitting node classifies
the packets into unique flows corresponding to the
communicating paths, through which the packets to be
transmitted pass, as a second criterion, and selects the
10 communicating path in retransmitting the packets
independently of the communicating path selected at the
time of the first transmission as a third criterion.

5 The communication method according to claim 3,
15 characterized in that the transmitting node and the
receiving node are connected via a plurality of
communicating paths, and the transmitting node classifies
the packets into the flows of which the number is fewer
than the number of the communicating paths, through which
20 the packets to be transmitted pass, as a second criterion,
and selects the communicating path in retransmitting the
packets independently of the communicating path selected
at the time of the first transmission as a third
criterion.

6 The communication method according to claim 1,
characterized in that the transmitting node is a
transmitting-side transferring node for transferring the
packet, transmitted by a separate communicating node, and
5 the receiving node is a receiving-side transferring node
for transferring the packet, received by a separate
communicating node.

7 The communication method according to claim 6,
10 characterized in that the transmitting node and the
receiving node are connected via one communicating path,
the second group flow of the transmitting node is
comprised of a single flow, and the packets are
transmitted by utilizing a single communicating path.

15

8 The communication method according to claim 6,
characterized in that the transmitting node and the
receiving node are connected via a plurality of
communicating paths, and the transmitting node classifies
20 the packets into unique flows corresponding to the
communicating paths, through which the packets to be
transmitted pass, as a second criterion, and selects the
communicating path in retransmitting the packets
independently of the communicating path selected at the
25 time of the first transmission as a third criterion.

9 The communication method according to claim 6,
characterized in that the transmitting node and the
receiving node are connected via a plurality of
5 communicating paths, and the transmitting node classifies
the packets into the flows of which the number is fewer
than the number of the communicating paths, through which
the packets to be transmitted pass, as a second criterion,
and selects the communicating path in retransmitting the
10 packets independently of the communicating path selected
at the time of the first transmission as a third
criterion.

10 The communication method according to claim 3,
15 characterized in that selection of the path or a decision
of a selection priority thereof is made in the
transmitting node as a third criterion of the transmitting
node, where path selection or path selection priority
update is performed upon every packet to be input, based
20 on path status information on a selectable path, based on
identification information on a time from which said path
status information is effective or on a transmitted packet,
and based on a transmission history after the time from
which said path status information is effective or a
25 transmission history after transmission of the packet

specified with transmitted packet identification
information.

11 The communication method according to claim 10,
5 wherein said path status information includes a delay of a
path.

12 The communication method according to claim 10,
wherein said path status information includes a
10 transmission rate of a path.

13 The communication method according to claim 10,
wherein said path status information includes a load of a
path.

15

14 The communication method according to claim 10,
further comprising the step of correcting a transmission
cost calculation result regarding a packet transmitted
before updating path status information of each path, when
20 the path status information is updated for path selection
or selection priority update.

15 The communication method according to claim 14,
further comprising the step of discarding a history prior
25 to a first packet transmitted on or after a time from

which the latest path status information is effective,
when a transmission cost calculation result of each path
is corrected.

- 5 **16** The communication method according to claim 10,
further comprising the step of selecting as a packet
transmission path a path having an earliest estimation
value of a reception completion time at a reception node.
- 10 **17** The communication method according to claim 10,
further comprising the step of selecting as a packet
transmission path a path having a largest estimation value
of a data amount, which can be completely received by a
specific time at a reception node.
- 15 **18** The communication method according to claim 10,
further the step of interrupting data transmission
according to an estimated current path status in each path.
- 20 **19** The communication method according to claim 18,
wherein a condition for interruption of said data
transmission is that an estimated reception completion
time is equal to or greater than a specific value.
- 25 **20** The communication method according to claim 10,

characterized in that path selection or a determination of a transmission interruption is made according to the policy, which differs every attribution of transmission data.

5

21 A node, said node being configured of a transmitting section for transmitting a packet and a receiving section for receiving the packet and taking a retransmitting control and a sequencing of the packet independently,

10 characterized in that:

said transmitting section includes:

a means for affixing to the transmission packet a first identifier, said first identifier being assigned in a one-to-one manner to each flow of a first group flow based upon a first criterion relating to a sequencing, a first sequential number, said first sequential number being unique within each flow belonging to said first group flow, a second identifier, said second identifier being assigned in a one-to-one manner to each flow of a second group flow based upon a second criterion relating to a retransmitting control, and a second sequential number, said second sequential number being unique within each flow belonging to said second group flow, to transmit it; and

25 a means for specifying the packet, for which

retransmission was requested by the node having received the packet, from said second identifier and second sequential number to retransmit its packet: and that

said receiving section includes:

5 a means for classifying all received packets based upon said second identifier to check the packets having the second sequential number, which were not received, with each second group flow to transmit its second identifier and second sequential number to the node having
10 transmitted the packet, and to request retransmission thereof; and

 a means for classifying all received packets based upon said first identifier to sequence the packets within each first group flow based upon said first sequential
15 number to perform a receiving process of the sequenced packets in the sequenced order.

22 The node according to claim 21, characterized in that each of nodes is connected to the other via one
20 communicating path, the second group flow is comprised of a single flow, and the packet is transmitted by utilizing a single communicating path.

23 The node according to claim 21, characterized in, in a
25 case where a plurality of communicating paths for

transmitting the packet exist, including a means for selecting the communicating path for transmitting the packet, based upon a third criterion relating to a schedule of the packet transmission.

5

24 The node according to claim 23, characterized in that each of the nodes is connected to the other via a plurality of communicating paths, and the packets are classified into unique flows corresponding to the communicating paths, through which the packets to be transmitted pass, as a second criterion, and the communicating path is selected in retransmitting the packets independently of the communicating path selected at the time of the first transmission as a third criterion.

10

15

25 The node according to claim 23, characterized in that, each of the nodes is connected to the other via a plurality of communicating paths, the packets are classified into the flows of which the number is fewer than the number of the communicating paths, through which the packets to be transmitted pass, as a second criterion, and the communicating path is selected in retransmitting the packets independently of the communicating path selected at the time of the first transmission as a third

20

25

criterion.

26 The node according to claim 21, characterized in that
the transmitting section of the node is a transferring-
5 side transferring node for transferring the packet
transmitted by a separate communicating node, and the
receiving section of the node is a receiving-side
transferring node for transferring the packet received by
a separate communicating node.

10

27 The node according to claim 26, characterized in that
each of the nodes is connected to the other via one
communicating path, the second group flow is comprised of
a single flow, and the packets are transmitted by
15 utilizing a single communicating path.

28 The node according to claim 26, characterized in that
each of the nodes is connected to the other via a
plurality of communicating paths, the packets are
20 classified into unique flows corresponding to the
communicating path, through which the packets to be
transmitted pass, as a second criterion, and the
communicating path is selected in retransmitting the
packets independently of the communicating path selected
25 at the time of the first transmission as a third

criterion.

29 The node according to claim 26, characterized in that
each of the nodes is connected to the other via a
5 plurality of communicating paths, the packets are
classified into the flows of which the number is fewer
than the number of the communicating paths, through which
the packets to be transmitted pass, as a second criterion,
and the communicating path is selected in retransmitting
10 the packets independently of the communicating path
selected at the time of the first transmission as a third
criterion.

30 The node according to claim 23, wherein said means for
15 selecting the communicating path makes selection of the
path or a decision of a selection priority thereof is made
in the transmitting node as a third criterion, where path
selection or path selection priority update is performed
upon every packet to be input, based on path status
20 information on a selectable path, based on identification
information on a time from which said path status
information is effective or on a transmitted packet, and
based on a transmission history after the time from which
said path status information is effective or a
25 transmission history after transmission of the packet

specified with transmitted packet identification
information.

31 The node according to claim 30, wherein said path
5 status information includes a delay of a path.

32 The node according to claim 30, wherein said path
status information includes a transmission rate of a path.

10 **33** The node according to claim 30, wherein said path
status information includes a load of a path.

34 The node according to claim 30, wherein said means for
selecting the communicating path corrects a transmission
15 cost calculation result regarding a packet transmitted
prior or updating when path status information of each
path is updated in the updating of path selection or
selection priority.

20 **35** The node according to claim 34, wherein said means for
selecting the communicating path discards a history before
a first transmitted packet validating latest path status
information when a transmission cost calculation result of
each path is corrected.

36 The node according to claim 30, wherein said means for selecting the communicating path selects as a packet transmission path a path having an earliest estimation value of a reception completion time at a reception node.

5

37 The node according to claim 30, wherein said means for selecting the communicating path selects as a packet transmission path a path having a largest estimation value of a data amount which can be completely received by a specific time at a reception node.

10

38 The node according to claim 30, wherein said means for selecting the communicating path interrupts data transmission according to an estimated current path status for each path.

15

39 The node according to claim 38, wherein a condition for interruption of said data transmission is that an estimated reception completion time is equal to or greater than a specific value.

20

40 The node according to claim 30, wherein said means for selecting the communicating path determines the interruption of path selection or transmission according to a policy different every attribute of a transmission

25

data.

41 A controlling program for a node, said node taking a retransmitting control and a sequencing of a packet
5 independently, characterized in that said controlling program causes said node to function as:

a means for affixing to the transmission packet a first identifier, said first identifier being assigned in a one-to-one manner to each flow of a first group flow
10 based upon a first criterion relating to a sequencing, a first sequential number, said first sequential number being unique within each flow belonging to said first group flow, a second identifier, said second identifier being assigned in a one-to-one manner to each flow of a
15 second group flow based upon a second criterion relating to a retransmitting control, and a second sequential number, said second sequential number being unique within each flow belonging to said second group flow, to transmit it;

20 a means for specifying the packet, for which retransmission was requested by the node having received the packet, from said second identifier and second sequential number to retransmit its packet;

a means for classifying all received packets based
25 upon said second identifier to check the packets having

the second sequential number, which were not received,
with each second group flow to transmit its second
identifier and second sequential number to the node having
transmitted the packet, and to request retransmission
5 thereof; and

a means for classifying all received packets based
upon said first identifier to sequence the packets based
upon said first sequential number with each first group
flow, and to perform a receiving process of the sequenced
10 packets in the sequenced order.

42 The controlling program for a node according to claim
41, characterized in each of nodes is connected to the
other via one communicating path, the second group flow is
15 comprised of a single flow, and the packet is transmitted
by utilizing a single communicating path.

43 The controlling program for a node according to claim
41, characterized in, in a case where a plurality of
20 communicating paths for transmitting the packet exist,
causing said node to function as a means for selecting the
communicating path for transmitting the packet based upon
a third criterion relating to a schedule of the packet
transmission.

44 The controlling program for a node according to claim 43, characterized in each of the nodes is connected to the other via a plurality of communicating paths, and the packets are classified into unique flows corresponding to
5 the communicating paths, through which the packets to be transmitted pass, as a second criterion, and the communicating path is selected in retransmitting the packets independently of the communicating path selected at the time of the first transmission as a third
10 criterion.

45 The controlling program for a node according to claim 43, characterized in that each of the nodes is connected to the other via a plurality of communicating paths, the
15 packets are classified into the flows of which the number is fewer than the number of the communicating paths, through which the packets to be transmitted pass, as a second criterion, and the communicating path is selected in retransmitting the packets independently of the
20 communicating path selected at the time of the first transmission as a third criterion.

46 The controlling program for a node according to claim 41, characterized in that the transmitting section of the
25 node is a transmitting-side transferring node for

transferring the packet, transmitted by a separate communicating node, and the receiving section of the node is a receiving-side transferring node for transferring the packet, received by a separate communicating node.

5

47 The controlling program for a node according to claim 46, characterized in that each of the nodes is connected to the other via one communicating path, the second group flow is comprised of a single flow, and the packets are
10 transmitted by utilizing a single communicating path.

48 The controlling program for a node according to claim 46, characterized in that each of the nodes is connected to the other via a plurality of communicating paths, the
15 packets are classified into unique flows corresponding to the communicating paths, through which the packets to be transmitted pass, as a second criterion, and the communicating path is selected in retransmitting the packets independently of the communicating path selected
20 at the time of the first transmission as a third criterion.

49 The controlling program for a node according to claim 46, characterized in that each of the nodes is connected
25 to the other via a plurality of communicating paths, the

packets are classified into the flows of which the number is fewer than the number of the communicating paths, through which the packets to be transmitted pass, as a second criterion, and the communicating path is selected
5 in retransmitting the packets independently of the communicating path selected at the time of the first transmission as a third criterion.

50 The controlling program for a node according to claim
10 43, characterized in causing said means for selecting the communicating path to make selection of the path or a decision of a selection priority thereof is made in the transmitting node as a third criterion, where path selection or path selection priority update is performed
15 upon every packet to be input, based on path status information on a selectable path, based on identification information on a time from which said path status information is effective or on a transmitted packet, and based on a transmission history after the time from which
20 said path status information is effective or a transmission history after transmission of the packet specified with transmitted packet identification information.

25 **51** The controlling program for a node according to claim

50, wherein said path status information includes a delay of a path.

52 The controlling program for a node according to claim
5 50, wherein said path status information includes a transmission rate of a path.

53 The controlling program for a node according to claim
50, wherein said path status information includes a load
10 of a path.

54 The controlling program for a node according to claim
50, further controlling said means for selecting the
communicating path so as to correct a transmission cost
15 calculation result regarding a packet transmitted prior or
updating when path status information of each path is
updated in the updating of path selection or selection
priority.

55 The controlling program for a node according to claim
20 54, further controlling said means for selecting the
communicating path so as to discard a history before a
first transmitted packet validating latest path status
information when a transmission cost calculation result of
25 each path is corrected.

56 The controlling program for a node according to claim
50, further controlling said means for selecting the
communicating path so as to select as a packet
5 transmission path a path having an earliest estimation
value of a reception completion time at a reception node.

57 The controlling program for a node according to claim
50, further controlling said means for selecting the
10 communicating path so as to select as a packet
transmission path a path having a largest estimation value
of a data amount which can be completely received by a
specific time at a reception node.

58 The controlling program for a node according to claim
15 50, further controlling said means for selecting the
communicating path so as to interrupt data transmission
according to an estimated current path status for each
path.

20

59 The controlling program for a node according to claim
58, wherein a condition for interruption of said data
transmission is that an estimated reception completion
time is equal to or greater than a specific value.

25

60 The controlling program for a node according to claim
50, further controlling said means for selecting the
communicating path so as to determine path selection or
transmission interruption according to a policy different
5 every attribute of transmission data.

61 A communicating method, characterized in affixing an
identifier for identifying a transmission flow and a
sequential number within said transmission flow to a
10 communication packet in addition to information for a
sequencing to take a retransmitting control thereof per
transmission flow on the receiving side, based upon said
identifier and said sequential number.

15 **62** A communicating method, characterized in affixing an
identifier for identifying a transmission flow and a
sequential number within said transmission flow to a
communication packet in addition to information for a
sequencing to detect a loss of the packet per transmission
20 flow on the receiving side, based upon said identifier and
said sequential number.

63 A node, characterized in including:
a means for affixing to the packet a first identifier,
25 said first identifier being assigned in a one-to-one

manner to each flow of a first group flow based upon a first criterion relating to a sequencing, a first sequential number, said first sequential number being unique within each flow belonging to said first group flow,
5 a second identifier, said second identifier being assigned in a one-to-one manner to each flow of a second group flow based upon a second criterion relating to a retransmitting control, and a second sequential number, said second sequential number being unique within each flow belonging
10 to said second group flow, to transmit it; and

a means for retransmitting the lost packets, which were detected, per transmission flow based upon said second identifier and said second sequential number.

15 **64** A controlling program of a node, characterized in causing said node to function as:

a means for affixing to the packet a first identifier, said first identifier being assigned in a one-to-one manner to each flow of a first group flow based upon a
20 first criterion relating to a sequencing, a first sequential number, said first sequential number being unique within each flow belonging to said first group flow, a second identifier, said second identifier being assigned in a one-to-one manner to each flow of a second group flow
25 based upon a second criterion relating to a retransmitting

control, and a second sequential number, said second sequential number being unique within each flow belonging to said second group flow, to transmit it; and

5 a means for retransmitting the lost packets, which were detected, per transmission flow based upon said second identifier and said second sequential number.